


EXECUTIVE SHINE

Floor Finish



For Use On

Vinyl	Rubber	Sealed Wood
Vinyl Asbestos	Concrete	Quarry Tile
Asphalt	Flagstone	
Linoleum	Brick	

Authorizations

Requires no authorization for use in U.S.D.A. offices and non-processing areas.

Product Description

A metal cross-linked, acrylic floor finish with high initial gloss and durability with exceptional responsiveness to spray buffing. Excellent for schools and institutions. A true workhorse in any maintenance program.

Directions For Use

PREPARATION: If stripping is necessary, use a high quality product and follow directions accordingly. If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow to dry completely.

FINISHING: If floor was stripped, use a good acrylic sealer to further prepare the floor for finishing. Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Two or three coats are desired initially, depending on the condition of the floor and gloss desired.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

Technical Data

TEST:

Nonvolatile Solids:

Color:

Odor:

Type:

pH:

Specular Gloss:

Slip Resistance:

Removability:

Detergent Resistance:

LIMIT:

18.0 ± 0.5%

Milky white

Mild

Metal crosslinked acrylic copolymers

8.5 - 9.0

Greater than 90

Greater than 0.50

With conventional strippers

Excellent

TEST:

Black Mark Resistance:

Leveling:

Sediment:

Recoat Time:

Buffability:

Storage Stability:

Weight Per Gallon:

Coverage:

Freeze/Thaw Stability:

Proper Shipping Name:

LIMIT:

Excellent

Excellent

0.1% by volume, max.

30 minutes

Spray buffable

2 years

8.60 lbs. per gallon

2000 - 2500 sq. ft. per gal.

Keep from freezing

Liquid floor wax

H. & M. Wagner & Sons

GLEN BURNIE, MD 21061

TO REORDER PHONE: (410) 766-1150

TOLL FREE WATTS: 800-492-4571 FAX: (410) 768-5822

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: Executive Shine Generic Name: Acrylic Floor Finish Chemical Family: Acrylic Wax Blend Formula: Proprietary	Supplier's Name: H. & M. Wagner & Sons Supplier's Address: Glen Burnie, MD 21061 Supplier's Phone #: (410) 768-5822
---	--

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Acrylic Copolymer Dispersion	63744-68-3	35 to 40			
Resin Solution	65405-63-2	5 to 10			
Polyethylene Wax Emulsion	68441-17-8	5 to 10			
Tributoxy Ethyl Phosphate	78-51-3	0 to 5			
Diethylene Glycol Monomethyl Ether	111-77-3	0 to 5			

SECTION 3-PHYSICAL DATA

SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Boiling Point (°F): 212 F. Vapor Pressure: 20mm Hg @ 68 F. % Volatile: 80+ Solubility in Water: Complete Physical Description: Thin milky liquid with characteristic odor.	Specific Gravity: 1.028 Vapor Density (Air=1): >1 pH: 8.5-9.0 Evaporation Rate (Water=1): <1	Flash Point (Method Used): N/A Upper Explosion Limit: N/A Extinguishing Media: N/A Special Firefighting Procedures: Non Flammable Unusual Fire and Explosion Hazards: N/A	Lower Explosion Limit: N/A
---	---	--	-----------------------------------

SECTION 5-REACTIVITY DATA

Stability: Stable Hazards Decomposition Products: Will not occur.	Hazardous Polymerization: None Incompatibility (Materials to Avoid): None
--	--

SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Avoid breathing of vapors. Use in well-ventilated area.

SECTION 7-HEALTH HAZARDS AND FIRST AID

SECTION 8-SPECIAL PROTECTION INFORMATION

Effects of Overexposure: Skin: Prolonged or repeated contact may cause dermatitis. Eyes: Eye irritant. May cause redness or swelling. Inhalation: Vapors irritating to nose, throat, lungs. May cause dizziness, headache, nausea. Ingestion: May be irritating to the mouth, throat, and gastrointestinal system. Vomiting and diarrhea expected with large doses.	Respiratory Protection: Use in well-ventilated area. Ventilation Requirements: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Chemical resistant rubber or neoprene. Eye Protection: Safety glasses or chemical splash goggles Other Protective Equipment: Eyewash should be nearby. Wear rubber boots and chemical resistant outerwear when using.
--	---

First Aid Procedures:

Skin: Flush with water. Seek medical attention if irritation persists.
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.
Inhalation: Remove victim to fresh air and monitor.
Ingestion: Dilute with 2 glasses of water. Seek medical attention if symptoms persist.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.
Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not disposal of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories: No - Fire Hazard No - Sudden Release of Pressure Hazard No - Reactivity Hazard Yes - Immediate (acute) Health Hazard No - Delayed (chronic) Health Hazard	Shipping Information: FOR CONTAINERS > 1 Gallon : Liquid Floor Wax FOR 1 GALLON CONTAINERS : Liquid Floor Wax FOR CONTAINERS < 1 GALLON : Liquid Floor Wax	HMIS Hazardous Materials Identification System <table border="1"> <tr> <td>Health</td> <td>1</td> </tr> <tr> <td>Flammability</td> <td>0</td> </tr> <tr> <td>Reactivity</td> <td>0</td> </tr> <tr> <td>Personal Protection</td> <td>A</td> </tr> </table>	Health	1	Flammability	0	Reactivity	0	Personal Protection	A
Health	1									
Flammability	0									
Reactivity	0									
Personal Protection	A									

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: CHEM-TEL, Inc. @ 800-255-3924 (24 hours, 7 days per week)

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight
	None	

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS#	Chemical Name	Percent by Weight
	None	

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product